



www.IAP-AirProducts.com • Sales@IAP-AirProducts.com

**Standard Fume Arm - Duct Diameter 6", Reach 14'**

- 301101509**
- Hood inlet Diameter 12".
  - Hanging model.

Previous Part #: • W02-01-1640

**Standard construction:**


- 530-825 cfm
- All adjustments on the outside
- Aluminum hood with air diverter
- Grab handle around the hood
- Aluminum hood joints
- Middle and swivel aluminum joints
- Aluminum and steel mounting swivel
- Smooth tubes
- Standard built-in air damper
- Black PVC flexible hoses (temperature resistance up to 176°F)
- Standard powder coating
- Mounting bracket WS-160
- Connection flange Ø6" steel

**Accessories and options:**

- Photosensor set, hood light, light switch, 26ft of cable
- Hood light set with switch and 26ft of cable
- Hood light set with 2 switches (additional switch for fan or electric damper control), 26ft of cable
- Extended hood Ø6" / 20"
- Mounting bracket WSD-160 (extended version)
- Extension Booms
- Fans
- Floor stanchions

**Notes:**

**The method of packing and carton sizes:**



A = 14.17"  
 B = 88.19"  
 H = 24.8"  
 weight = 55 lbs

All dimensions are given in [inch].

888-372-0050 x4  
 Industrial Air Products  
 2544 Highway 70 East  
 Cookeville, TN 38506  
 © All rights reserved.

