



www.IAP-AirProducts.com • Sales@IAP-AirProducts.com

Standard Fume Arm - Duct Diameter 8", Reach 10'

- 301101513**
- Hood inlet Diameter 14".
 - Hanging model.

Previous Part #: • W02-01-2030

Standard construction:


- 825-1470 cfm
- All adjustments on the outside
- Aluminum hood with air diverter
- Grab handle around the hood
- Aluminum hood joints
- Middle and swivel aluminum joints
- Aluminum and steel mounting swivel
- Smooth tubes
- Standard built-in air damper
- Black PVC flexible hoses (temperature resistance up to 80°C)
- Standard powder coating
- Mounting bracket WS-200
- Connection flange Ø8" steel

Accessories and options:

- Photosensor set including hood light kit, light switch, 26ft of cable
- Hood light set with switch and 26ft of cable
- Hood light set with 2 switches (additional switch for fan or electric damper control), 26ft of cable
- Extended hood Ø8"/20"
- Extension booms
- Fans
- Floor stanchions

Notes:

The method of packing and carton sizes:



A = 15.35"
 B = 77.95"
 H = 27.56"
 weight = 66 lbs

All dimensions are given in [inch].



888-372-0050 x4
 Industrial Air Products
 2544 Highway 70 East
 Cookeville, TN 38506
 © All rights reserved.

