



www.IAP-AirProducts.com • Sales@IAP-AirProducts.com

Boxair M2 - cassette filter unit

102758

- main filter cassette 180 ft²
- fan 3 HP, 60 Hz, 3-phase, 480 V
- UL/CSA motor

Mobile filter unit for sporadic use where there is no need of constant exhaust operation for two workstations.

Standard construction:

- aluminum impeller 3 HP fan unit
- two stage filtration
- filter indicator
- heavy duty welded and powder coated construction
- power cord holder
- two 6" inlets

Parameters:

Nominal Airflow:	1180 cfm
Main cartridge surface:	180 ft ²
Weight:	185 lbs
Power Supply:	480V / 60Hz
Motor Power:	3 HP
Rated Current:	4.9 A


Accessories and options:

- IAP 6" fume arm, reach 7', hood inlet 12"
- IAP 6" fume arm, reach 10', hood inlet 12"

Spare parts:

- Cassette filter F9
- Metal mesh pre-filter G2
- Swivel caster with brake 80
- Fixed caster wheel 80

The method of packing and carton sizes:



A = 25.59"
 B = 28.35"
 H = 44.80"
 waga = 198.42 lbs

All dimensions are given in [inch].



Industrial Air Products
 2475 Hidden Cove Rd.
 Cookeville, TN 38506
 tel. 931-372-0050 fax. 931-372-0051
 © All rights reserved.

