



www.IAP-AirProducts.com • Sales@IAP-AirProducts.com

Stainless Steel Fume Arm - Duct Diameter 4", Reach 5'

W02-FS-1015

- Hood inlet Diameter 8".
- Hanging model.

Standard construction:


- nominal airflow 205-325 cfm
- all adjustments on the outside
- stainless steel hood with air diverter
- grab handle around the hood
- aluminum hood joints
- middle and swivel steel joints
- aluminum and stainless steel mounting swivel
- smooth stainless steel tubes
- stainless steel built-in air damper
- clear FDA polyurethane flexible hoses (temperature resistance up to 176°F)
- grade 304 stainless steel
- mounting bracket WSS-100 stainless steel
- connection flange Ø4" stainless steel
- stainless steel hardware nut, bolts and anodized aluminum shock assembly

Accessories and options:

- photosensor set, hood light, light switch, 26ft of cable
- hood light set with switch and 26ft of cable
- hood light set with 2 switches (additional switch for fan or electric damper control), 26ft of cable
- floor stanchions

Notes:

The method of packing and carton sizes:



A = 11.02"
B = 41.34"
H = 18.9"
weight = 20 lbs

All dimensions are given in [inch].



888-372-0050 x4
Industrial Air Products
2544 Highway 70 East
Cookeville, TN 38506
© All rights reserved.

