



www.IAP-AirProducts.com • Sales@IAP-AirProducts.com

Stainless Steel Fume Arm - Duct Diameter 6", Reach 14'

- W02-FS-1640**
- Hood inlet Diameter 12".
 - Hanging model.

Standard construction:


- nominal airflow 825-1470 cfm
- all adjustments on the outside
- stainless steel hood with air diverter
- grab handle around the hood
- aluminum hood joints
- middle and swivel aluminum joints
- aluminum and stainless steel mounting swivel
- smooth stainless steel tubes
- standard built-in air damper
- clear FDA polyurethane flexible hoses (temperature resistance up to 176°F)
- stainless steel grade 304
- mounting bracket WSS-200
- connection flange Ø6" stainless steel
- stainless steel hardware nut, bolts and anodized aluminum shock assembly

Accessories and options:

- photosensor set, hood light, light switch, 26ft of cable
- hood light set with switch and 26ft of cable
- hood light set with 2 switches (additional switch for fan or electric damper control), 26ft of cable
- extended hood Ø6"/20"
- mounting bracket WSSD-160 stainless steel (extended version)
- extension Booms
- fans
- floor stanchions

Notes:

The method of packing and carton sizes:



A = 14.17"
 B = 88.19"
 H = 24.8"
 weight = 68.6 lbs

All dimensions are given in [inch].



888-372-0050 x4
 Industrial Air Products
 2544 Highway 70 East
 Cookeville, TN 38506
 © All rights reserved.

