



www.IAP-AirProducts.com • Sales@IAP-AirProducts.com

Standard Fume Arm - Duct Diameter 6", Reach 10'

- 301101508**
- Hood inlet Diameter 12".
 - Standing model.

Previous Part #: • W02-01-1630P

Standard construction:


- 530-825 cfm
- all adjustments on the outside
- aluminum hood with air diverter
- grab handle around the hood
- aluminum hood joints
- middle and swivel aluminum joints
- aluminum and steel mounting swivel
- smooth tubes
- standard built-in air damper
- black PVC flexible hoses (temperature resistance up to 176°F)
- standard powder coating

Accessories and options:

- photosensor set including hood light kit, light switch, 26ft of cable
- hood light set with switch and 26ft of cable
- hood light set with 2 switches (additional switch for fan or electric damper control), 26ft of cable
- grounding option - all metal parts hood, tubes, mounting swivel connected with grounding wires
- extended hood Ø6"20" (adds to the price of arm or standard hood)

Notes:

The method of packing and carton sizes:



A = 13.54"
 B = 66.54"
 H = 24.8"
 weight = 51 lbs

All dimensions are given in [inch].

888-372-0050 x4
 Industrial Air Products
 2544 Highway 70 East
 Cookeville, TN 38506
 © All rights reserved.

